

Amendments to the Claims:

1. (Currently Amended) An apparatus comprising:
a processor; and
a memory including computer program code, the memory and computer program code configured to, with the processor, cause the apparatus to at least ~~perform the following~~:
~~receiving~~ receive a connection request via a network across which an originating client is configured to communicate;
~~preparing~~ prepare a network-independent trigger for transmission to a terminal in response to ~~receiving~~ receipt of the connection request; and
~~receiving~~ receive a registration message, in response to the trigger, from the terminal via the network to thereby register the terminal with the apparatus and acquire a network-dependent identity of the terminal to thereby enable establishment of a communication session with the terminal based upon the network-dependent identity of the terminal.
2. (Currently Amended) An apparatus according to Claim 1, wherein ~~receiving the apparatus being caused to receive~~ receiving the apparatus being caused to receive a connection request comprises ~~receiving the apparatus being caused to receive~~ receiving the apparatus being caused to receive a connection request from the originating client, and wherein the memory and computer program code are further configured to, with the processor, cause the apparatus to further ~~perform~~ preparing prepare the connection request for transmission to the terminal after registering the terminal.
3. (Currently Amended) An apparatus according to Claim 2, wherein ~~preparing the apparatus being caused to prepare~~ preparing the apparatus being caused to prepare the connection request comprises ~~preparing the apparatus being caused to prepare~~ preparing the apparatus being caused to prepare the connection request for transmission to the terminal through at least one other apparatus.
4. (Previously Presented) An apparatus according to Claim 1, wherein the apparatus is embodied in a Session Initiation Protocol (SIP) proxy.

5. (Currently Amended) An apparatus according to Claim 1, wherein ~~receiving the apparatus being caused to receive~~ a connection request comprises ~~receiving the apparatus being caused to receive~~ a connection request, and thereafter ~~causing cause~~ the connection request to be stored in a buffer, and wherein ~~preparing the apparatus being caused to prepare~~ the connection request comprises ~~retrieving the apparatus being caused to retrieve~~ the connection request from the buffer and thereafter ~~preparing prepare~~ the connection request for transmission to the terminal based upon the network-dependent identity of the terminal.

6. (Currently Amended) An apparatus according to Claim 1, wherein ~~receiving the apparatus being caused to receive~~ a registration message comprises ~~receiving the apparatus being caused to receive~~ a registration message from the terminal via at least one of a network address translator (NAT) or a firewall (FW) operating between the apparatus and the terminal, and wherein ~~preparing the apparatus being caused to prepare~~ a network-independent trigger comprises ~~preparing the apparatus being caused to prepare~~ a network-independent trigger for transmission in a manner independent of the at least one of the NAT or FW.

7. (Currently Amended) An apparatus according to Claim 1, wherein ~~receiving the apparatus being caused to receive~~ a registration message comprises ~~receiving the apparatus being caused to receive~~ a subsequent registration message, and wherein the memory and computer program code are further configured to, with the processor, cause the apparatus to further perform the following:

~~receiving receive~~ a first registration message from the terminal before ~~preparing preparation of the network-independent trigger~~ for transmission to thereby register the terminal with the apparatus, wherein the first registration message includes a network-independent identity of the terminal,

and wherein ~~preparing the apparatus being caused to prepare~~ a network-independent trigger comprises ~~preparing the apparatus being caused to prepare~~ a network-independent trigger for transmission based upon the network-independent identity of the terminal.

8. (Currently Amended) An apparatus according to Claim 1, wherein ~~preparing the apparatus being caused to prepare~~ a network-independent trigger comprises ~~preparing the apparatus being caused to prepare~~ a network-independent trigger for transmission to the terminal via a network across which an originating client is configured to at least one of directly or indirectly communicate.

9. (Previously Presented) An apparatus according to Claim 8, wherein the network comprises at least one of a public network or a private network.

10. (Currently Amended) An apparatus comprising:
a processor; and
a memory including computer program code, the memory and computer program code configured to, with the processor, cause the apparatus to at least perform the following:
~~receiving~~ receive a registration message via a network across which an originating client is configured to communicate, wherein ~~receiving the apparatus being caused to receive a registration message comprises receiving the apparatus being caused to receive a registration message from a terminal to thereby register the terminal with the apparatus, and wherein the registration message includes a network-independent identity of the terminal; and~~
~~preparing~~ prepare a network-independent trigger for transmission to the terminal based upon the network-independent identity of the terminal to thereby trigger the terminal to update registration of the terminal with the apparatus, including acquisition by the apparatus of a network-dependent identity of the terminal to thereby enable establishment of a communication session with the terminal based upon the network-dependent identity of the terminal.

11. (Currently Amended) An apparatus according to Claim 10, wherein the memory and computer program code are further configured to, with the processor, cause the apparatus to further perform the following:

~~receiving~~ receive a connection request, the trigger being prepared for transmission in

response to ~~receiving receipt of~~ the connection request; and

~~preparing prepare~~ the connection request for transmission to the terminal after acquiring acquisition of the network-dependent identity of the terminal.

12. (Currently Amended) An apparatus according to Claim 11, wherein ~~preparing the apparatus being caused to prepare~~ the connection request comprises ~~preparing the apparatus being caused to prepare~~ the connection request for transmission to the terminal through at least one other apparatus.

13. (Currently Amended) An apparatus according to Claim 11, wherein ~~receiving the apparatus being caused to receive~~ a connection request comprises ~~receiving the apparatus being caused to receive~~ a connection request, and thereafter ~~causing cause~~ the connection request to be stored in a buffer, and wherein ~~preparing the apparatus being caused to prepare~~ the connection request for transmission comprises ~~retrieving the apparatus being caused to retrieve~~ the connection request from the buffer and thereafter ~~preparing prepare~~ the connection request for transmission to the terminal based upon the network-dependent identity of the terminal to thereby enable establishment of the communication session.

14. (Previously Presented) An apparatus according to Claim 10, wherein the apparatus is embodied in a Session Initiation Protocol (SIP) proxy.

15. (Currently Amended) An apparatus according to Claim 10, wherein ~~receiving the apparatus being caused to receive~~ a registration message comprises ~~receiving the apparatus being caused to receive~~ a registration message from the terminal via at least one of a network address translator (NAT) or a firewall (FW) operating between the apparatus and the terminal, and wherein ~~preparing the apparatus being caused to prepare~~ a network-independent trigger comprises ~~preparing the apparatus being caused to prepare~~ a network-independent trigger for transmission to the terminal in a manner independent of the at least one of the NAT or the FW.

16. (Currently Amended) An apparatus according to Claim 10, wherein ~~receiving the apparatus being caused to receive~~ a registration message comprises ~~receiving the apparatus being caused to receive~~ a first registration message, and wherein the memory and computer program code are further configured to, with the processor, cause the apparatus to further perform the following:

~~receiving~~ receive a subsequent registration message from the terminal in response to the trigger being sent to the terminal to thereby update registration of the terminal and acquire the network-dependent identity of the terminal, thereby enabling establishment of a communication session with the terminal based upon the network-dependent identity of the terminal.

17. (Currently Amended) An apparatus according to Claim 10, wherein ~~receiving the apparatus being caused to receive~~ a registration message comprises ~~receiving the apparatus being caused to receive~~ a registration message via a network across which an originating client is configured to at least one of directly or indirectly communicate.

18. (Previously Presented) An apparatus according to Claim 17, wherein the network comprises at least one of a public network or a private network.

19. (Previously Presented) A method comprising:
receiving a connection request at an apparatus via a network across which an originating client is configured to communicate;
preparing a network-independent trigger for transmission from the apparatus to a terminal in response to receiving the connection request; and
receiving a registration message, in response to the trigger, at the apparatus from the terminal via the network to thereby register the terminal with the apparatus and acquire a network-dependent identity of the terminal to thereby enable establishment of a communication session with the terminal based upon the network-dependent identity of the terminal.

20. (Previously Presented) A method according to Claim 19, wherein receiving a connection request comprises receiving a connection request at the apparatus from the originating client, the method further comprising preparing the connection request for transmission to the terminal after registering the terminal.

21. (Previously Presented) A method according to Claim 20, wherein preparing the connection request comprises preparing the connection request for transmission from the apparatus to the terminal through at least one other apparatus.

22. (Previously Presented) A method according to Claim 20, wherein receiving a connection request comprises receiving a connection request, and thereafter causing the connection request to be stored in a buffer, and wherein preparing the connection request comprises retrieving the connection request from the buffer and thereafter preparing the connection request for transmission to the terminal based upon the network-dependent identity of the terminal.

23. (Previously Presented) A method according to Claim 19, wherein preparing a trigger for transmission to the terminal comprises preparing a trigger for transmission to the terminal from an apparatus comprising a Session Initiation Protocol (SIP) proxy.

24. (Previously Presented) A method according to Claim 19, wherein receiving a registration message comprises receiving a registration message at the apparatus from the terminal via at least one of a network address translator (NAT) or a firewall (FW) operating between the apparatus and the terminal,

and wherein preparing a network-independent trigger comprises preparing a network-independent trigger for transmission in a manner independent of the at least one of the NAT or FW.

25. (Previously Presented) A method according to Claim 19, wherein receiving a

registration message comprises receiving a subsequent registration message, wherein the method further comprises:

receiving a first registration message at the apparatus from the terminal before preparing the network-independent trigger for transmission to thereby register the terminal with the apparatus, wherein the first registration message includes a network-independent identity of the terminal,

and wherein preparing a network-independent trigger comprises preparing a network-independent trigger for transmission based upon the network-independent identity of the terminal.

26. (Previously Presented) A method according to Claim 19, wherein preparing a network-independent trigger comprises preparing a network-independent trigger for transmission to the terminal via a network across which an originating client is configured to at least one of directly or indirectly communicate.

27. (Previously Presented) A method according to Claim 26, wherein the network comprises at least one of a public network or a private network.

28. (Previously Presented) A method comprising:
receiving a registration message at an apparatus via a network across which an originating client is configured to communicate, wherein receiving a registration message comprises receiving a registration message from a terminal to thereby register the terminal with the apparatus, and wherein the registration message includes a network-independent identity of the terminal; and

preparing a network-independent trigger for transmission to the terminal based upon the network-independent identity of the terminal to thereby trigger the terminal to update registration of the terminal with the apparatus, including acquisition by the apparatus of a network-dependent identity of the terminal to thereby enable establishment of a communication session with the terminal based upon the network-dependent identity of the terminal.

29. (Previously Presented) A method according to Claim 28 further comprising:
receiving a connection request at the apparatus from the originating client, the trigger
being prepared for transmission in response to receiving the connection request; and
preparing the connection request for transmission from the apparatus to the terminal after
acquiring the network-dependent identity of the terminal.

30. (Previously Presented) A method according to Claim 29, wherein preparing the
connection request comprises preparing the connection request for transmission from the
apparatus to the terminal through at least one other apparatus.

31. (Previously Presented) A method according to Claim 29, wherein receiving a
connection request comprises receiving a connection request, and thereafter causing the
connection request to be stored in a buffer, and wherein preparing the connection request
comprises retrieving the connection request from the buffer and thereafter preparing the
connection request for transmission to the terminal based upon the network-dependent identity of
the terminal to thereby enable establishment of the communication session.

32. (Previously Presented) A method according to Claim 28, wherein receiving a
registration message at an apparatus comprises receiving a registration message at an apparatus
comprising a Session Initiation Protocol (SIP) proxy.

33. (Previously Presented) A method according to Claim 28, wherein receiving a
registration message comprises receiving a registration message at an apparatus from the
terminal via at least one of a network address translator (NAT) or a firewall (FW) operating
between the apparatus and the terminal,
and wherein preparing a network-independent trigger comprises preparing a network-
independent trigger for transmission to the terminal in a manner independent of the at least one
of the NAT or the FW.

34. (Previously Presented) A method according to Claim 28, wherein receiving a registration message comprises receiving a first registration message, and wherein the method further comprises:

receiving a subsequent registration message at the apparatus from the terminal in response to the trigger being sent to the terminal to thereby update registration of the terminal and acquire the network-dependent identity of the terminal, thereby enabling establishment of a communication session with the terminal based upon the network-dependent identity of the terminal.

35. (Previously Presented) A method according to Claim 28, wherein receiving a registration message comprises receiving a registration message via a network across which an originating client is configured to at least one of directly or indirectly communicate.

36. (Previously Presented) A method according to Claim 35, wherein receiving a registration message comprises receiving a registration message via in a network comprising at least one of a public network or a private network.

37. (Currently Amended) An apparatus comprising:

a processor; and

a memory including computer program code, the memory and computer program code configured to, with the processor, cause the apparatus to at least ~~perform the following~~:

~~receiving~~ receive a trigger from another apparatus operating in a network across which an originating client is configured to communicate, the trigger comprising a network-independent trigger; and in response to ~~the receiving~~ receipt of the trigger,

~~preparing~~ prepare a registration message for transmission to the other apparatus via the network to thereby register the apparatus with the other apparatus and acquire a network-dependent identity of the apparatus to thereby enable establishment of a communication session with the apparatus based upon the network-dependent identity of the apparatus.

38. (Currently Amended) An apparatus according to Claim 37, wherein ~~receiving the~~
~~apparatus being caused to receive~~ a trigger comprises ~~receiving the apparatus being caused to~~
~~receive~~ a trigger in response to the other apparatus receiving a connection request from the
originating client, and wherein the memory and computer program code are further configured
to, with the processor, cause the apparatus to further ~~perform receiving~~ ~~receive~~ the connection
request from the other apparatus after ~~registering~~ ~~registration of~~ the apparatus.

39. (Currently Amended) An apparatus according to Claim 38, wherein ~~receiving the~~
~~apparatus being caused to receive~~ the connection request comprises ~~receiving the apparatus being~~
~~caused to receive~~ the connection request from the other apparatus via at least one further
apparatus.

40. (Currently Amended) An apparatus according to Claim 38, wherein ~~receiving the~~
~~apparatus being caused to receive~~ a trigger comprises ~~receiving the apparatus being caused to~~
~~receive~~ a trigger in response to the other apparatus receiving, and thereafter storing in a buffer, a
connection request from the originating client, and wherein ~~preparing the apparatus being caused~~
~~to prepare~~ a registration message comprises ~~preparing the apparatus being caused to prepare~~ a
registration message for transmission to the other apparatus to thereby enable the other apparatus
to retrieve the connection request from the buffer and thereafter send the connection request to
the apparatus based upon the network-dependent identity of the apparatus.

41. (Currently Amended) An apparatus according to Claim 37, wherein ~~receiving the~~
~~apparatus being caused to receive~~ a trigger comprises ~~receiving the apparatus being caused to~~
~~receive~~ a trigger from another apparatus comprising a Session Initiation Protocol (SIP) proxy.

42. (Currently Amended) An apparatus according to Claim 37, wherein ~~preparing the~~
~~apparatus being caused to prepare~~ a registration message comprises ~~preparing the apparatus~~
~~being caused to prepare~~ a registration message for transmission to the other apparatus via at least

one of a network address translator (NAT) or a firewall (FW) operating between the other apparatus and the apparatus,

and wherein ~~receiving the apparatus being caused to receive~~ a trigger comprises ~~receiving the apparatus being caused to receive~~ a trigger in a manner independent of the at least one of the NAT or the FW.

43. (Currently Amended) An apparatus according to Claim 37, wherein ~~preparing the apparatus being caused to prepare~~ a registration message comprises ~~preparing the apparatus being caused to prepare~~ a subsequent registration message for transmission, and wherein the memory and computer program code are further configured to, with the processor, cause the apparatus to further perform:

~~preparing prepare~~ a first registration message for transmission to the other apparatus before ~~receiving receipt of~~ the trigger to thereby register the apparatus with the other apparatus, wherein the first registration message includes a network-independent identity of the apparatus to thereby enable the processor to receive the network-independent trigger based upon the network-independent identity of the apparatus.

44. (Currently Amended) An apparatus according to Claim 37, wherein ~~receiving the apparatus being caused to receive~~ a trigger comprises ~~receiving the apparatus being caused to receive~~ a trigger from another apparatus operating in a network across which an originating client is configured to at least one of directly or indirectly ~~communicating~~ communicate.

45. (Currently Amended) An apparatus according to Claim 44, wherein ~~receiving the apparatus being caused to receive~~ a trigger comprises ~~receiving the apparatus being caused to receive~~ a trigger from another apparatus operating in a network comprising at least one of a public network or private network.

46. (Currently Amended) An apparatus comprising:
a processor; and

a memory including computer program code, the memory and computer program code configured to, with the processor, cause the apparatus to at least ~~perform the following~~:

~~preparing~~ prepare a registration message for transmission to another apparatus operating in a network across which an originating client is configured to communicate, wherein ~~preparing the apparatus being caused to prepare~~ a registration message comprises ~~preparing the apparatus being caused to prepare~~ a registration message for transmission via the network to thereby register the apparatus with the other apparatus, wherein the registration message includes a network-independent identity of the apparatus; and

~~receiving~~ receive a network-independent trigger based upon the network-independent identity of the apparatus to thereby trigger the apparatus to update registration of the apparatus with the other apparatus, including acquisition of a network-dependent identity of the apparatus to thereby enable establishment of a communication session with the apparatus based upon the network-dependent identity of the apparatus.

47. (Currently Amended) An apparatus according to Claim 46, wherein ~~receiving the apparatus being caused to receive~~ a network-independent trigger comprises ~~receiving the apparatus being caused to receive~~ a network-independent trigger in response to the other apparatus receiving a connection request from the originating client, and wherein the memory and computer program code are further configured to, with the processor, cause the apparatus to further ~~perform receiving~~ receive the connection request from the other apparatus after ~~registering~~ registration of the apparatus with the other apparatus.

48. (Currently Amended) An apparatus according to Claim 47, wherein ~~receiving the apparatus being caused to receive~~ the connection request comprises ~~receiving the apparatus being caused to receive~~ the connection request from the other apparatus node via at least one further apparatus.

49. (Currently Amended) An apparatus according to Claim 47, wherein ~~receiving the apparatus being caused to receive~~ a network-independent trigger comprises ~~receiving the~~

apparatus being caused to receive a network-independent trigger in response to the other apparatus receiving, and thereafter storing in a buffer, the connection request, and wherein receiving the apparatus being caused to receive the connection request comprises receiving the apparatus being caused to receive the connection request from the other apparatus, the other apparatus having retrieved the connection request from the buffer and thereafter sent the connection request to the apparatus based upon the network-dependent identity of the apparatus.

50. (Currently Amended) An apparatus according to Claim 46, wherein ~~preparing the apparatus being caused to prepare a registration message comprises preparing the apparatus being caused to prepare a registration message for transmission to another apparatus comprising a Session Initiation Protocol (SIP) proxy.~~

51. (Currently Amended) An apparatus according to Claim 46, wherein ~~preparing the apparatus being caused to prepare a registration message comprises preparing the apparatus being caused to prepare a registration message for transmission to another apparatus via at least one of a network address translator (NAT) or a firewall (FW) operating between the other apparatus and the apparatus,~~

~~and wherein receiving the apparatus being caused to receive a network-independent trigger comprises receiving the apparatus being caused to receive a network-independent trigger in a manner independent of the at least one of the NAT or the FW.~~

52. (Currently Amended) An apparatus according to Claim 46, wherein ~~preparing the apparatus being caused to prepare a registration message comprises preparing the apparatus being caused to prepare a first registration message for transmission to another apparatus to thereby register the apparatus with the other apparatus, and wherein the memory and computer program code are further configured to, with the processor, cause the apparatus to further perform preparing prepare a subsequent registration message for transmission to the other apparatus in response to receiving receipt of the trigger to thereby update registration of the apparatus and acquire the network-dependent identity of the apparatus to thereby enable~~

establishment of a communication session with the apparatus based upon the network-dependent identity of the apparatus.

53. (Currently Amended) An apparatus according to Claim 46, wherein ~~preparing the apparatus being caused to prepare~~ a registration message comprises ~~preparing the apparatus being caused to prepare~~ a registration message for transmission to another apparatus operating in a network across which an originating client is configured to at least one of directly or indirectly communicate.

54. (Currently Amended) An apparatus according to Claim 46, wherein ~~preparing the apparatus being caused to prepare~~ a registration message comprises ~~preparing the apparatus being caused to prepare~~ a registration message for transmission to another apparatus operating in a network comprising at least one of a public network or a private network.